

Wire controls & thermostats for hydronic terminals

Airmust 3V A1 / 010 A1

Touch screen control for wall installation



- Color touch screen 3.5" TFT
- Power supply 230V
- European standard mounting
- ModBus
- Wi-Fi connectivity 2.4G
- APP available for Android and iOS: My House Pro
- 3-speed version (3V) or for 0-10V version (010)
- 2 pipes and 4 pipes systems
- Dry input for window contact
- Water probe inlet
- Automatic brightness
- Room temperature probe
- Relative humidity probe
- Management of the mode of operation
- Temperature and humidity history display
- Automatic change from summer to winter
- Automatic management of the time change (legal/solar)
- Multilanguage
- Weekly calendar
- Weekly time schedule



Airmust BMCP A1

Touch screen thermostat for on-board installation of the VSL model fan coil machine



- LCD display with five touch function keys
- Power supply 230V
- Wall mounting
- ModBus
- Wi-Fi connectivity 2.4G
- App available on the stores for Android and iOS: Tuya
- For 3-speed fan coils
- For 2-tube and 4-tube systems
- Entry contact window
- Water probe inlet
- Ambient temperature sensor
- Management of the mode of operation
- Automatic change from summer to winter
- Weekly calendar
- Weekly time schedule



Airmust P

Touch screen thermostat for wall installation



- LCD display with five touch function keys
- Power supply 230V
- Wall mounting
- ModBus
- Wi-Fi connectivity 2.4G
- APP available on the Android and iOS stores: Tuya
- For 3-speed fan coils
- For 2-tube and 4-tube systems
- Entry contact window
- Water probe inlet
- Ambient temperature sensor
- Management of the mode of operation
- Automatic change from summer to winter
- Weekly calendar
- Weekly time schedule



CBP

Electronic thermostat for wall installation



- Configurable digital fan coil thermostat diamond new line like TFF01M, but suitable for driving of 0-10V actuators.
- Driving of fan motor via 3 relays or proportional via 0..10V signal
- Possibility to supply the fan motor with 230V~, thermostat and actuators with 24V~.
- Temperature indication in °C or °F.
- Clean contact input for bimetallic minimum temperature (TMB)
- Analog input for water temperature probe (SND-W4)
- Wide configurability for 2-4 pipe systems, with or without neutral zone

CRA

Thermostat for wall installation



- Wall mounted thermostat 230V
- Contacts relays 5A/230V
- Selector fan 3 speeds
- Off-on manual switch
- Management of the 2-tube system with or without on-off valves 230V

Compatibility table

	CRA	CBP	AIRMUST BMCP A1	AIRMUST P	AIRMUST 3V A1	AIRMUST 010 A1
GRIMPER MSL	X	X	X	■ (3)	■ (3)	X
GRIMPER VSL	X	X	■ (3)	X	X	X
GRIMPER BSL	X	X	X	■ (3)	■ (3)	X
VE: VMI, VMF, OMP, OMI	■	■	X	■ (1)	■ (1)	X
VE: VII, VIF, OIP, OII	■	■	X	■ (1)	■ (1)	X
VE: VMI, VMF, OMP, OMI Vers. MB	■	■	X	X	X	■ (1) (4)
VE: VII, VIF, OIP, OII Vers. MB	■	■	X	X	X	■ (1) (4)
HCN	■ (2)	■ (2)	X	■ (1) (2)	■ (1) (2)	X
HCN - Vers. MB	X	■	X	X	X	■ (1) (4)
HCNP	■ (2)	■ (2)	X	■ (1) (2)	■ (1) (2)	X
HCNP - Vers. MB	X	■ (4)	X	X	X	■ (1) (4)
HCNA	■ (2)	■ (2)	X	■ (1) (2)	■ (1) (2)	X
HCNA - Vers. MB	X	■ (4)	X	X	X	■ (1) (4)

(1) Not compatible with TMB - SND-A3 accessory required

(2) Check power consumption, add SDI accessory if necessary

(3) If necessary add STSL accessory for winter minimum temperature management

(4) SDI Accessory not required

Compatible ■
Not compatible X